



A TUCKER AUTO-MATION HOLDINGS COMPANY

WWW.TUCKERZAP.COM

Contact Information:

Tucker Auto-Mation ZAP Supply, LLC

Location: 11075 Parker Drive
Irwin, PA 15642

Toll Free: 1-855-8 TUCKER

Tel: 412-823-2537

Fax: 412-816-1862

Technical Support: 1-888-467-5751

Email: sales@tuckerzap.com

TUCKER ZAP ACCESSORIES

8830 Battery Back Up

Tucker ZAP PATENT NUMBER / TITLE / REGISTRATION DATE:

USA 8,182,381 | Drive arrangement | May 22, 2012
USA 8,115,438 | Aperture closure member control arrangements | Feb. 14, 2012
USA 8,033,374 | Drive arrangement | Oct. 11, 2011
USA 7,633,253 | Control and monitoring arrangements for an aperture closure member | Dec. 15, 2009
USA 7,437,971 | Drive arrangement | Oct. 21, 2008
USA 7,333,308 | Control arrangement | Feb. 19, 2008
USA 7,005,884 | Monitoring apparatus for monitoring electrical drive current for an electric motor | Feb. 28, 2006
USA 6,188,198 | Aperture closures | Feb. 13, 2001

Mexico 243645 | Aparato de monitoreo | Feb. 6, 2007
Canada 2445152 | Monitoring apparatus | June 25, 2013
Canada 2440772 | Control arrangement | June 21, 2011
Canada 2560530 | Drive arrangement | May 21, 2013
Canada 2641641 | Aperture closures | April 26, 2011
Canada 2445123 | Drive arrangement | Feb. 16, 2010
Canada 2338191 | Aperture closures | Dec. 30, 2008



ZAP Part# 8830

Description:

The 8830 Commercial Operator Battery Back Up system is designed for use with all standard ZAP Commercial operators. Zap Controllers provide a constant charge to the battery system and automatically engage them in the event a power interruption and automatically disengage and resume charging upon restoration of the power supply.

Wiring requirements:

18 AWG/6

Power requirement:

16VDC Provided from controller

Mounting type:

Wall mount

Terminal plug:

6 Position Dual Direction slide in plug

Voltage output:

12VDC, 24VDC, 48VDC

Battery type:

Sealed Lead Acid

Charging system:

Current Limited Constant Voltage
Short Circuit and Reverse Connection Proof

Run time average:

10 Cycles

Dimensions:

Height: 8.5"
Width: 6.5"
Depth: 4.25"

Operating temp:

-13 deg F to + 149 deg F

Works with:

All standard commercial ZAP Controllers



ZAP Controls
8830 Battery Back up

8830 USA



WWW.TUCKERZAP.COM